

## 4K Interactive Touch Display Narrow Bezel Design



Upgrade the touch display  
with an OPS PC



MTC 4K Interactive Touch Display adopts Projected Capacitive Touch Technology (P-Cap), allowing more accurate and flexible operation. It helps to enhance the presentation experience in conferences, large audience-based seminars and events. The narrow bezel design offers a seamless viewing experience to captivate your audience.

### Features:

- Narrow bezel design
- UHD technology to deliver vivid images
- Plug & play enables easy usage with any device/operating system: PC, Mac, Android and iOS
- 10 & 20-point multi-touch and P-Cap touch technology enable superb collaborative and interactive experience.
- The optional Open Pluggable Specification (OPS) allows users to easily operate an interactive presentation and collaboration. It is compatible with Microsoft Windows or other OS. With OPS, users can download any software or application without connection to any external computer or device.

Specification		IDP65KXPC4K	IDP75KXPC4K	IDP86KXPC4K	IDP98KXPC4K
Physical Parameters	Unit Dimensions(LxHxD)	1497 x 954 x 95mm	1736 x 1101 x 110mm	1990 x 1245 x 106mm	2264 x 1361 x 97mm
	Package Dimensions(LxHxD)	1630 x 1030 x 230mm	1990 x 1315 x 350mm	2200 x 1370 x 360mm	2517 x 1825 x 552mm
	Net Weight	45KG	63KG	76KG	162KG
	Gross Weight	52KG	81KG	100KG	214KG (with Pallet)
	VESA	400 x 200mm	600 x 400mm	700 x 400mm	800 x 600mm
Panel Parameters	Panel Size	65"	75"	86"	98"
	Backlight	LED			
	Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	Brightness	Type: 350 cd/m <sup>2</sup>			Type: 500 cd/m <sup>2</sup>
	Contrast	5000:1	4000:1	1300:1	1300:1
	Visible Angle	178° / 178°			
	Refreshing Frequency	60Hz			120HZ
	Response Time	8ms		6.5ms	5ms
	Display Colors	1.07B			
Touch Technology	Touch Technology	Projected capacitive touch			
	Touch Mode	Fingers or capacitive stylus pens			
	Touch Response Time	≤ 10ms		≤ 10ms	< 12ms
	Touch Points	20	10		20
	Touch Precision	1 pt : ±1mm, 10pt : ±2.5mm			
Functional Interfaces	HDMI	HDMI x 2(in), HDMI x 1(front in)			HDMI x 4(in), HDMI x 1(out)
	VGA	VGA x 1			
	AV	AV composite video x 1(in)			
	USB	USB 3.0 x 2(rear), USB 2.0 x 1(front)			
	Other	Ypbpr x 1, SD x 1, RS232 x 1, Earphone x 1(out)			
	Network Port	RJ45 x 1			
	Speaker	Internal speaker, 2 x 10W			
	Main Unit Support Format	JPG, BMP, PNG, MPEG-1/2/4, RM, RMVB, MJPEG, FLV, MOV, VCI, DivXFLV, MP3, M4A(AAC)			
Electrical and Operation Parameters	Working Voltage	100 - 240AC ( 50 - 60Hz)			
	Power	<250W	<300W	<450W	<540W
	Service Life	30000hr			
	Working Temperature	0°C-40°C			
	Working Relative Humidity	10%-90%			
Accessories		Power cord, Remote control, WIFI antenna, Pen x 2, HDMI cable(3m), USB cable(3m), Handle x 2, Operation manual			
OPS System (Not included in the display, Optional to purchase)		OPS i3 CPU, 4G, 256G HD (not include OS) OPS i5 CPU, 4G, 256G HD (not include OS) OPS i7 CPU, 4G, 256G HD (not include OS)			