

## 4K Interactive Touch Display Narrow Bezel Design



Upgrade the touch display  
with an OPS PC



MTC 4K Interactive Touch Display adopts Projected Capacitive Touch Technology (P-Cap), allowing more accurate and flexible operation. It helps to enhance the presentation experience in conferences, large audience-based seminars and events. The narrow bezel design offers a seamless viewing experience to captivate your audience.

### Features:

- Narrow bezel design
- UHD technology to deliver vivid images
- Plug & play enables easy usage with any device/operating system: PC, Mac, Android and iOS
- 10 & 20-point multi-touch and P-Cap touch technology enable superb collaborative and interactive experience.
- The optional Open Pluggable Specification (OPS) allows users to easily operate an interactive presentation and collaboration. It is compatible with Microsoft Windows or other OS. With OPS, users can download any software or application without connection to any external computer or device.

| Specification   |  | IDP65KXPC4K                                 | IDP75KXPC4K         | IDP86KXPC4K                                  | IDP98KXPC4K                 |
|---|--|---|---------------------|--|-----------------------------|
| Physical Parameters   | Unit Dimensions(LxHxD)   | 1497 x 954 x 95mm                           | 1736 x 1100 x 108mm | 1989 x 1245 x 106mm                          | 2264 x 1361 x 96mm          |
|   | Package Dimensions(LxHxD)  | 1630 x 1030 x 230mm                         | 1990 x 1315 x 350mm | 2200 x 1370 x 360mm                          | 2517 x 1825 x 552mm         |
|   | Net Weight   | 45KG  | 63KG                | 76KG   | 162KG                       |
|   | Gross Weight   | 52KG  | 81KG                | 100KG  | 214KG                       |
| Panel Parameters  | VESA   | 400 x 200mm                                 | 600 x 400mm         | 700 x 400mm                                  | 800 x 600mm                 |
|   | Panel Size   | 65"   | 75"                 | 86"  | 98"                         |
|   | Backlight  | LED   |                     |  |                             |
|   | Resolution   | 3840 x 2160                                 | 3840 x 2160         | 3840 x 2160                                  | 3840 x 2160                 |
|   | Brightness   | Type: 350 cd/m <sup>2</sup>                 |                     |  | Type: 500 cd/m <sup>2</sup> |
|   | Contrast   | 5000:1                                      | 1200:1              | 1300:1                                       | 1300:1                      |
|   | Visible Angle  | 178° / 178°                                 |                     |  |                             |
|   | Refreshing Frequency   | 60Hz  |                     |  | 120HZ                       |
|   | Response Time  | 8ms   |                     | 6.5ms  | 5ms                         |
| Touch Technology  | Display Colors   | 1.07B                                       |                     |  |                             |
|   | Touch Technology   | Projected capacitive touch                  |                     |  |                             |
|   | Touch Mode   | Fingers or capacitive stylus pens           |                     |  |                             |
|   | Touch Points   | 20  |                     |  |                             |
| Functional Interfaces   | Touch Precision  | 1.5mm                                       |                     |  |                             |
|   | HDMI   | HDMI X 3(in)                                |                     | HDMI x 4(In), HDMI X 1(Out)                  |                             |
|   | AV   | AV X 1(in)                                  |                     | AV x 1(in), AV x 1(out)                      |                             |
|   | VGA  | VGA X 1 (in)                                |                     | VGA X 1(in)                                  |                             |
|   | Y PB PR  | --  |                     | Y PB PR X 1(in)                              |                             |
|   | USB  | MEDIA-USB X 3<br>PC-USB X 1<br>TOUCH-USB X1 |                     | MEDIA-USB X 4<br>PC-USB X 2<br>TOUCH-USB X 4 |                             |
|   | RS232  | RS232 x 1(in)                               |                     | RS232 x 1(in), R232 X 1(out)                 |                             |
|   | TV   | TV X 1(in)                                  |                     |  |                             |
|   | Speaker  | Internal speaker, 2 x 10W                   |                     |  |                             |
|   | Other  | Earphone x 1(out)                           |                     |  |                             |
| Electrical and Operation Parameters                               | Working Voltage  | 100 - 240AC (50 /60Hz)                      |                     |  |                             |
|   | Power  | <350W                                       | <450W               | <500W  | <540W                       |
|   | Service Life   | 30000hr                                     |                     |  |                             |
|   | Working Temperature  | 0°C-40°C                                    |                     |  |                             |
|   | Working Relative Humidity  | 20%-80%                                     |                     |  |                             |
| Accessories   | Power cord, Pen x 2, HDMI cable, USB cable, Handle x 2, Operation manual             |   |                     |  |                             |
| OPS System<br>(Not included in the display, Optional to purchase) | OPS i3 CPU, 4G, 256G HD (not include OS)<br>OPS i5 CPU, 4G, 256G HD (not include OS) |   |                     |  |                             |