

## 4K P-cap Interactive Touch Display Narrow Bezel Design



Upgrade the touch display  
with an OPS PC



MTC 4K Interactive Touch Display adopts Projected Capacitive Touch Technology (P-Cap), allowing more accurate and flexible operation. It helps to enhance the presentation experience in conferences, large audience-based seminars and events. The narrow bezel design offers a seamless viewing experience to captivate your audience.

### Features:

- Narrow bezel design.
- UHD technology to deliver vivid images.
- Plug & play enables easy usage with any device/operating system: PC, Mac, Android and iOS.
- 10 points (in Android) & 20 points (in Windows 10) multi-touch and P-Cap touch technology enable superb collaborative and interactive experience.
- The optional Open Pluggable Specification (OPS) allows users to easily operate an interactive presentation and collaboration. It is compatible with Microsoft Windows or other OS. With OPS, users can download any software or application without connection to any external computer or device.

Specification		IDP65KXPC4KC	IDP75KXPC4KC	IDP86KXPC4KC	
Display	Panel Size	65"	75"	86"	
	Backlight	D-LED			
	Resolution	3840 x 2160			
	Brightness (typ.)	400cd/m <sup>2</sup> (typ.)	450 cd/m <sup>2</sup> (typ.)	400cd/m <sup>2</sup> (typ.)	
	Contrast Ratio	4000:1	1400:1	1200:1	
	Visible Angle	H 178° / V 178°			
	Refreshing Frequency	60Hz			
	Response Time	8ms			
	Colors	1.07B			
	Life Time	30,000hrs (min)			
Touch Technology	Surface Treatment	Anti-Glare glass, 4mm			
	Touch Mode	Fingers or capacitive stylus pen			
	Touch Points	10 (Android), 20 (Windows 10)			
	Touch Response Time	10ms			
Operation System	Touch Precision	1.5mm			
	Android Vesion	Android 8.0			
	CPU	Quad Core A53			
	CPU working frequency	1.5GHz			
	RAM	4GB DDR4			
Functional and Control Interfaces	ROM	32GB			
	Compatible Operation System	Windows 10			
	HDMI In	x2			
	HDMI Out	x1			
	DP In	x1			
	AV In	x1			
	YPbPr in	x1			
	VGA In	x1			
	PC Audio In	x1			
	Earphone Out	x1			
	Speaker (Internal)	10W X 2pcs			
	TF Card	x1			
	Media USB	x2 (USB3.0 x1 + USB2.0 x1)			
	Touch USB	x3 (HDMI 1 Touch x1 + HDMI 2 Touch x1 + VGA/DP Touch x1)			
	LAN	x1 (RJ45)			
	Wifi	Yes			
	RS232	x1 (DB9)			
	Electrical	Power Requirement	100 ~ 240AC (50/60Hz)		
		Power Consumption	≤350W	≤400W	≤550W
		Standby Power Consumption	≤ 0.5W		
Working Environment & Installation	Working Temperature	0°C ~ 40°C			
	Storage Temperature	-20°C ~ 60°C			
	Working Humidity	20% ~ 80% (Non-Condensing)			
	Storage Humidity	10% ~ 90% (Non-Condensing)			
	Orientation	Landscape-oriented installation			
Physical	Product Dimensions (WxDxH) mm	1525.4 x 89.6 x 912.2	1746.9 x 101.5 x 1037.7	1996.2 x 109.5 x 1174.4	
	Packaging Dimensions (WxDxH) mm	1670 x 300 x 1100	1960 x 300 x 1280	2180 x 320 x 1400	
	Net Weight	49kg	65.5kg	86.6kg	
	Gross Weight	60.5kg	85.5kg	114.5kg	
	Mounting VESA	600mm x 400mm (M8)	600mm x 400mm (M8)	700mm x 400mm (M8)	
Accessories		Power cord, Pen x2, HDMI cable, USB cable, WiFi Antenna x4, Operation manual			
OPS Compatibility (Not included in the display, Optional to purchase)		OPS i3 CPU, 4G, 256G HD (not include OS) OPS i5 CPU, 4G, 256G HD (not include OS) OPS i7 CPU, 4G, 256G HD (not include OS)			

Remark: All features and specifications are subject to change without notice.